

Turbojet roterbar brenner


Turbojet



System



Anslutning:



EU
7/16"

US
1"



- For alle typer lodding, myk lodding og varmeapplikasjoner.


Turbojet Roterbar Brenner	
Arbeidstrykk, bar	0-3,5
Brennerdiameter Ø, mm	14x2
Gassforbruk g/t	590
Effekt, kW	7,6
Myklodding maks Ø, mm	60
Hardlodding maks Ø, mm	25

Anslutning	Art nr.
EU 7/16" Pizotenning	264112
US (E400) Pizotenning	264133

System



Anslutning:



EU
7/16"

US
1"



- For alle typer lodding, myk lodding og varmeapplikasjoner.

Turbojet Roterbar Brenner	
Arbeidstrykk, bar	0-3,5
Brennerdiameter Ø, mm	14
Gassforbruk g/t	295
Effekt, kW	3,8
Myklodding maks Ø, mm	40
Hardlodding maks Ø, mm	18

Anslutning	Art nr.
EU 7/16" Pizotenning	261012
US (E400)	262033
US (E400)	261033

Light line brenner

- Spiss brenner
- Presis flammejustering
- Messing



For bruk med engangsflaske 220983.



Beskyttelse for gulv og vegg på lodding. Sparer tid og varme.
For temperaturer opp til 760 ° C.

Light line brenner nr.	881647
------------------------	--------

Lødmatte nr.	415061
Størrelse:	25x25 cm